

# Self Contained Compactor

with Side Feed Doghouse

Designed for volume  
usage in:  
Apartments  
Restaurants  
Hospitals  
Supermarkets,  
Hotels &  
More...

[CompactorMC.com](http://CompactorMC.com)



The SCS line offers a visually appealing, high performance compactor designed to reduce hauling costs and increase the aesthetic appeal of your business with its Unique Radial Body Design. With a special liquid seal, the SCS series of compactors are designed to meet your needs, whatever they may be.

**Benefits:**

- High Compaction Reduces Hauling Costs
- Reduces Visible Refuse
- Saves Employee's Time
- Eliminates Fluid Leakage

Rental and leasing programs offered!



Please Recycle

Made in the US

# Self-Contained Compactor with Side Feed Doghouse



## Technical Specifications

### Optional Equipment

One+ account management  
Remote controls  
Multi-cycle options  
Programmable controlled systems  
Oil heater

Spray deodorizer unit  
Through-the-wall installation kits  
Hydraulic cart-dump systems  
Various hopper configurations

Model	Body Capacity	Loading Height A	Overall Length B	Maximum Height w/ Wheels C	Compactor Mod. Width D	Maximum Body Width E
SCS10	10 cu. yds	42"	16'5"	6'1 1/2"	74"	96"
SCS12	12 cu. yds	42"	16'5"	7'1 1/2"	74"	96"
SCS15	15 cu. yds	42"	18'5"	7'1 1/2"	74"	96"
SCS20	20 cu. yds	42"	20'5"	8'1 1/2"	74"	96"
SCS25	25 cu. yds	42"	22'11"	8'1 1/2"	74"	96"
SCS30	30 cu. yds	42"	24'5"	8'1 1/2"	74"	96"
SCSC??	custom	custom	custom	custom	custom	custom

### Additional Specs

#### 2.0 Cubic yard charging chamber

Dimensions: ..... 41" x 68" x 24.5H"  
Penetration: ..... 13"  
Ram face: ..... 3/8" plate  
Chamber sides: ..... 1/4" plate  
Chamber floor: ..... 3/8" plate

#### Motor:

10HP, 208/230/460V. 3PH: 60HZ

115 V control circuit

Key lock power-on switch

PLC for control functions

Pump: ..... 10 GPM

#### Cylinder:

Twin: ..... 4" bore cylinder  
Stroke: ..... 36"  
Rod size: ..... 2 1/4"

Approximate cycle time: ..... 40 seconds

Normal compaction force: ... 40,250 lbs

#### Container:

10 ga. Radius Body design  
Bubble gate to assist material roll  
Rear gate sealed up to 24" STD

Fluid filled pressure gauge

Full container light

Advanced-warning light

